

## **FISH EYE ELIMINATOR**

### **DESCRIPTION**

FISH EYE ELIMINATOR is a special liquid additive that is formulated to allow epoxy systems to flow out on silicone or oil contaminated substrates, including existing epoxy and urethane floors. The additive decreases fish eye and/or cratering by lowering the surface tension of the product to which it is added. This helps prevent beading of the liquid on the contaminated substrate.

FISH EYE ELIMINATOR is a good product to have when installing floors in machine shops, body shops, automobile prep/delivery areas, and plastics processing facilities. Using FISH EYE ELIMINATOR for oil-contaminated substrates is not a substitute for soaking, scrubbing and rinsing with HI-SPEED Cleaner/Degreaser. Most of the contamination should be removed using HI-SPEED.

### **PACKAGING**

FISH EYE ELIMINATOR is available in 1-quart cans and 1-gallon cans.

### **MIXING INFORMATION**

FISH EYE ELIMINATOR should be added sparingly to DUR-A-GLAZE #4, DUR-A-GARD, DUR-A-GLAZE, NOVOLAC, DUR-A-GLAZE KF, and ELAST-O-COAT. The small amount of the additive will not disturb the proper ratio of the hardener and resin blend. Add  $\frac{3}{4}$  - 1  $\frac{1}{2}$  ounce per 1  $\frac{1}{2}$  gallon of blended epoxy and mix well. Use 50% less FISH EYE ELIMINATOR for second coat if needed.

### **PRECAUTIONS**

All equipment that comes into direct contact with FISH EYE ELIMINATOR including roller frames, mixing attachments, pails etc, must be disposed of. Re-using the equipment will introduce silicone contaminants on the next job and could cause fisheye problems.

### **CAUTION**

**Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. KEEP OUT OF REACH OF CHILDREN.**

*Before using any DUR-A-FLEX, Inc. product, be sure the Material Safety Data Sheet is read and understood.*