

Accelera Colorants SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Accelera Colorants

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: February 28, 2015

2. HAZARD(S) IDENTIFICATION

Classification:

Physical	Health
Not Hazardous	Skin Sensitization Category 1 Specific Target Organ Toxicity Repeat Exposure Category 1 Carcinogen Category 1A

Labeling:

Danger!



Hazard statement(s)

May cause an allergic skin reaction.
May cause cancer by inhalation
Causes damage to lung through prolonged or repeated exposure by inhalation

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood
Do not breathe dust.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical attention.
IF exposed or concerned: Get medical attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical attention.
Store locked up.

Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Carbon Black	1333-86-4	0-100%
Titanium Dioxide	13463-67-7	0-100%
Barium Sulfate	7727-43-7	0-100%
CI Pigment Black 28	68186-91-4	0-100%
CI Blue Pigment 36	68187-11-1	0-100%
CI Green Pigment 50	68186-85-6	0-100%
CI Pigment Brown 24	68186-90-3	0-100%
Chromium oxide	1308-38-9	0-100%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Remove victim to fresh air. Seek medical attention if irritation or other symptoms develop.

Skin contact: Remove contaminated clothing. Wash with soap and water. If irritation or rash develops, get medical attention.

Eye contact: Flush eyes thoroughly with large amounts of water, holding eyelids open. If irritation occurs and persists, seek medical attention.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

Most important symptoms/effects, acute and delayed: Dust may cause eye and respiratory irritation. May cause mechanical skin irritation. May cause an allergic skin reaction. Prolonged inhalation of dust may cause lung damage.

Indication of immediate medical attention and special treatment, if necessary: None required under normal conditions of use.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use media appropriate for the surrounding fire.

Specific hazards arising from the chemical: Combustion may produce carbon and metal oxides.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing as described in Section 8. Avoid breathing dust.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and materials for containment and cleaning up: Scoop or sweep up and place into a container for disposal. Avoid generating dust.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Do not breathe dust. Wash thoroughly after handling. Use with adequate ventilation.

Conditions for safe storage, including any incompatibilities: No special storage required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Carbon Black	3.5 mg/m ³ TWA OSHA PEL 3 mg/m ³ TWA ACGIH TLV
Titanium Dioxide	15 mg/m ³ TWA OSHA PEL (total dust) 10 mg/m ³ TWA ACGIH TLV
Barium Sulfate	5 mg/m ³ TWA OSHA PEL (respirable fraction) 15 mg/m ³ TWA OSHA PEL (total dust) 5 mg/m ³ TWA ACGIH TLV (inhalable fraction)
CI Pigment Black 28	0.5 mg/m ³ TWA OSHA PEL (as inorganic Cr compounds) 0.5 mg/m ³ TWA ACGIH TLV (as inorganic Cr compounds) 1 mg/m ³ TWA OSHA PEL (as Cu dust and mists) 1 mg/m ³ TWA ACGIH TLV (as Cu dust and mists)
CI Blue Pigment 36	0.5 mg/m ³ TWA OSHA PEL (as inorganic Cr compounds) 0.5 mg/m ³ TWA ACGIH TLV (as inorganic Cr compounds) 0.1 mg/m ³ TWA OSHA PEL (as Co dust and fumes) 0.02 mg/m ³ TWA ACGIH TLV (as Co metal and inorganic compounds)
CI Green Pigment 50	0.1 mg/m ³ TWA OSHA PEL (as Co dust and fumes) 0.02 mg/m ³ TWA ACGIH TLV (as Co metal and inorganic compounds) 1 mg/m ³ TWA OSHA PEL (as Ni metal and insoluble compounds) 0.2 mg/m ³ TWA ACGIH TLV (as Ni metal and insoluble compounds)
CI Pigment Brown 24	0.5 mg/m ³ TWA OSHA PEL (as inorganic Cr compounds) 0.5 mg/m ³ TWA ACGIH TLV (as inorganic Cr compounds) 0.5 mg/m ³ TWA OSHA PEL (as Sb compounds) 0.5 mg/m ³ TWA ACGIH TLV (as Sb compounds)
Chromium Oxide	0.5 mg/m ³ TWA OSHA PEL (as inorganic Cr compounds) 0.5 mg/m ³ TWA ACGIH TLV (as inorganic Cr compounds)

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Personal Protective Equipment:

Respiratory protection: If the exposures limits are exceeded, a NIOSH approved respirator with a dust/mist filter or supplied air respirator is recommended. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Impervious gloves such as rubber are recommended to prevent skin contact

Eye protection: Chemical safety glasses with sideshields are recommended to avoid eye contact. .

Other: None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Colored powder.

Odor: No odor

Odor threshold: Not available	pH: Not applicable
Melting Point/Freezing Point: Not available	Boiling Point: Not applicable
Flash point: Not applicable	Evaporation rate: Not applicable
Flammability (solid, gas): Not flammable	
Flammable limits: LEL: Not applicable	UEL: Not applicable
Vapor pressure: Not applicable	Vapor density: Not applicable
Relative density: >1	Solubility(is): Negligible
Partition coefficient: n-Octanol/water: Not applicable	Auto-ignition temperature: Not applicable
Decomposition temperature: Not available	Viscosity: Not applicable

10. STABILITY AND REACTIVITY

Reactivity: None known.

Chemical stability: Stable.

Possibility of hazardous reactions: Not expected to be reactive.

Conditions to avoid: None known.

Incompatible materials: None known.

Hazardous decomposition products: None known.

11. TOXICOLOGICAL INFORMATION

Inhalation: Excessive inhalation of dust may cause upper respiratory tract irritation, coughing and difficulty in breathing.

Ingestion: Swallowing may cause gastrointestinal irritation and nausea.

Skin contact: May cause mechanical skin irritation. May cause an allergic skin reaction.

Eye contact: May cause mechanical irritation with redness and tearing.

Chronic effects from short- and long-term exposure: Prolonged inhalation of respirable dust may cause adverse lung effects.

Reproductive Toxicity: This product is not expected to cause adverse reproductive or developmental effects.

Sensitization: This product has not been shown to cause sensitization in animals or humans.

Mutagenicity: This product is not expected to cause mutagenic activity.

Carcinogenicity: This product contains nickel, and cobalt compounds. Nickel is listed by IARC as a “Possibly Carcinogenic to Humans”, Group 2B, by NTP as “Known to be a Human Carcinogen” and by ACGIH as a “Confirmed Human Carcinogen”, A1. Cobalt compounds and carbon black are listed by IARC as a “Possibly Carcinogenic to Humans” and by ACGIH as a “Confirmed Animal Carcinogen, A3. Titanium dioxide is listed by IARC as a “Possibly Carcinogenic to Humans”, Group 2B. None of the other components are listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Carbon Black: Oral rat LD50 > 8000 mg/kg, Inhalation rat LC50 > 4.6 mg/m³/4 hr.
 Titanium Dioxide: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >6.82 mg/L/4 hr
 Barium Sulfate: Oral rat LD50 307 g/kg, Dermal rat LD50 >2000 mg/kg
 CI Pigment Black 28: Oral rat LD50 > 10000 mg/kg, Inhalation rat LC50 >11.1 mg/L/4 hr
 CI Blue Pigment 36: Oral rat LD50 > 10000 mg/kg, Inhalation rat LC50 >5.05 mg/L/4 hr
 CI Green Pigment 50: Oral rat LD50 > 10000 mg/kg
 CI Pigment Brown 24: Oral rat LD50 > 10000 mg/kg
 Chromium oxide: Oral rat LD50 >15000 mg/kg, Inhalation rat LC50 >5.41 mg/L/4 hr

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Carbon Black: 96 hr LC0 Danio rerio 1000 mg/L, 24 hr EC50 daphnia magna > 5600 mg/L, EC50 Desmodesmus subspicatus > 10000 mg/L
 Titanium Dioxide: 96 hr LC50 Pimephales promelas >1000 mg/L, 48 hr EC50 daphnia magna >1000 mg/L, 72 hr EC50 Pseudokirchneriella subcapitata 61 mg/L
 Barium Sulfate: 96 he LC50 Danio rerio >3.5 mg/L, 48 hr EC50 daphnia magna 14500 ug/L, 72 he EC50 Pseudokirchnerella subcapitata > 1.15 mg/L
 CI Pigment Black 28: No data available
 CI Blue Pigment 36: No data available
 CI Green Pigment 50: 96 hr LC50 Leuciscus idus>10000mg/L, 48 hr EC50 daphnia magna >100 mg/L, 72 hr EC50 Desmodesmus subspicatus >100 mg/L
 CI Pigment Brown 24: 96 hr LC50 Leuciscus idus>10000mg/L, 48 hr EC50 daphnia magna >100 mg/L, 72 hr EC50 Desmodesmus subspicatus >100 mg/L
 Chromium oxide: 96 hr LC50 >10000 mg/L, 72 hr EC50 Desmodesmus subspicatus >848.6 mg/L

Persistence and degradability: Biodegradation is not applicable to inorganic substances.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None
IMDG	None	Not Regulated	None	None	None

IATA	None	Not Regulated	None	None	None
-------------	------	---------------	------	------	------

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health, Chronic Health

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

CI Pigment Black 28 (chromium III, copper compounds)	68186-91-4	0-100%
CI Blue Pigment 36 (chromium III, cobalt compounds)	68187-11-1	0-100%
CI Green Pigment 50 (cobalt, nickel, zinc compounds)	68186-85-6	0-100%
CI Pigment Brown 24 (antimony, chromium III compounds)	68186-90-3	0-100%
Barium Sulfate (barium compounds)	7727-43-7	0-100%

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects):

Carbon black	1333-86-4	0-100%	cancer
Titanium dioxide	13463-67-7	0-100%	cancer
CI Green Pigment 50 (Nickel compounds)	68186-85-6	0-100%	cancer

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian WHMIS Classification: Class D Division 2A (Very toxic material causing other toxic effects), Class D Division 2B (Toxic material causing other toxic effects)

This product has been classified under the CPR and this SDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 1 Flammability = 0 Instability = 0
HMIS Rating: Health = 2* Flammability = 0 Physical Hazard = 0

SDS Revision History: Converted to GHS format. All sections revised.

Date of preparation: February 28, 2015

Date of last revision: New SDS

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND USE.

Accelera Hardener SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Accelera Hardener

Product Code:

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: January 6, 2014

2. HAZARD(S) IDENTIFICATION

This product is one part of a 3 part product. Read and understand the hazard information on the SDS for Accelera Resin before using this product.

Classification:

Physical	Health
Not Hazardous	Acute Toxicity Category 4 - Inhalation Skin Sensitization Category 1 Respiratory Sensitization Category 1 Specific Target Organ Toxicity – Single Exposure Category 3 (Respiratory Irritation)

Labeling:

Danger!



Hazard statement(s)

Harmful by inhalation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.

Precautionary statement(s)

Avoid breathing mist, vapors and spray.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
In case of inadequate ventilation wear respiratory protection
Wear protective gloves.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If experiencing respiratory symptoms: Call a POISON CENTER.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical attention.
 Take off contaminated clothing and wash it before reuse.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Homopolymer of Hexamethylene Diisocyanate	28182-81-2	95-100%
Hexamethylene-1,6-Diisocyanate	822-06-0	<0.15%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Immediately remove to fresh air. If breathing is difficult have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get immediate medical attention. Asthma-like symptoms may develop immediately or delayed up to several hours.

Skin contact: Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. If rash or irritation develops, get medical attention. Launder clothing before re-use.

Eye contact: Immediately flush with large quantities of water for 15 minutes, holding the eyelids apart. Get medical attention if irritation develops.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. DO NOT INDUCE VOMITING. Get medical attention.

Most important symptoms/effects, acute and delayed: May be irritating to eyes, skin and respiratory system. May cause allergic skin and respiratory reaction. If an allergic respiratory reaction occurs, get immediate medical attention. Symptoms may be delayed. Individuals sensitized to isocyanates may have a life-threatening allergic reaction.

Indication of immediate medical attention and special treatment, if necessary: If skin or respiratory sensitization occurs, get immediate medical attention. Symptoms may be delayed for several hours after exposure. Respiratory sensitization may be life threatening.

Notes to Physicians: If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. This compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Inducing vomiting is contraindicated because of the irritating nature of the compound. There is no specific antidote for ingestions. An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate. Treatment is essentially symptomatic.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use foam, carbon dioxide and dry chemical. Use water spray for large fires. Cool fire exposed containers with water.

Specific hazards arising from the chemical: This product reacts with water producing heat and gases. Reaction may be violent. Closed containers may rupture when exposed to extreme heat or contaminated with water. Combustion may produce isocyanate vapors and other irritating, highly toxic gases. Exposure to heated diisocyanates can be extremely dangerous.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Do not allow run-off from fire fighting to enter drains or water courses. Decontaminate equipment and protective clothing before reuse.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing as described in Section 8. Isolate the area and prevent access. Ventilate and remove ignition sources.

Methods and materials for containment and cleaning up: Contain and collect with an inert absorbent. Neutralize with a decontamination solution made up of 80% water and 20% non-ionic surfactant (such as Plurafac SL-60 or Tergitol TMN-10) or 90% water and 3-8% ammonium hydroxide or concentrated ammonia and 2% detergent. Wait 15 minutes. Collect into an open-head metal container. Repeat until the surface is completely decontaminated. Cover loosely with lid and allow container to vent for 72 hours to allow carbon dioxide to escape.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe vapors or mists. Use only with adequate ventilation. Wear respiratory protection if material is heated, sprayed, used in a confined space, or if the exposure limit is exceeded. Warning properties are not adequate to prevent overexposure from inhalation. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash thoroughly after handling. Do not breathe smoke and gases created by overheating or burning this material. Decomposition products can be highly toxic and irritating.

Conditions for safe storage, including any incompatibilities: Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Protect from physical damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Homopolymer of Hexamethylene Diisocyanate	0.5 mg/m3 TWA Manufacturer 1.0 mg/m3 STEL Manufacturer
Hexamethylene-1,6-Diisocyanate	0.005 ppm TWA ACGIH TLV 0.02 ppm Ceiling Manufacturer

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

Individual protection measures, such as personal protective equipment:

Respiratory protection: If the exposure limits are exceeded or if exposure levels are unknown, a NIOSH approved positive pressure air supplied respirator with a full facepiece or air supplied hood should be used.

In some situations where exposure levels are known to be below 10 times the exposure limit an air purifying respirator (organic vapor with particulate prefilter) can be used. A change schedule for cartridges is required. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Wear impervious gloves such as butyl rubber, neoprene or nitrile rubber.

Eye protection: Chemical safety goggles recommended.

Other: Impervious clothing as needed to prevent contact. An eye wash should be available in the immediate work area.

Medical Surveillance: A pre-placement physical should be given to all employees that will work with isocyanates. Employees with a prior isocyanate sensitization should be excluded from working with this product. A history of adult asthma, eczema and respiratory allergies are possible reasons for excluding or restricting the employee from working with this product. A comprehensive annual medical surveillance program should be instituted for all employees who work with isocyanates. Once a worker has been diagnosed as sensitized, no further exposure can be permitted.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Pale yellow liquid

Odor: Odorless

Odor threshold: 0.01 (HDI)	pH: Not applicable
Melting Point/Freezing Point: -59.8°F / -51°C	Boiling Point: Decomposes
Flash point: 442.4 °F / 228°C	Evaporation rate: Not applicable
Flammability (solid, gas): Not flammable	
Flammable limits: LEL: Not applicable	UEL: Not applicable
Vapor pressure: Not applicable	Vapor density: Not applicable
Relative density: 1.17 @ 20°C	Solubility(is): Insoluble in Water
Partition coefficient: n-Octanol/water: logPow: 9.81 (calculated)	Auto-ignition temperature: >392°F / 200°C
Decomposition temperature: 482°F / 250°C (calculated)	Viscosity: 3,000 mPas@23°C

10. STABILITY AND REACTIVITY

Reactivity: None known.

Chemical stability: Stable

Possibility of hazardous reactions: Contact with water or temperatures above 350°F may cause polymerization.

Conditions to avoid: Avoid contact with heat, sparks and flames. Protect from freezing.

Incompatible materials: Avoid contact with water, alcohols, amines, bases and copper alloys.

Hazardous decomposition products: Thermal decomposition may produce carbon and nitrogen oxides, hydrogen cyanide and isocyanic acid.

11. TOXICOLOGICAL INFORMATION

Inhalation: Inhalation of vapors or mists may cause mucous membrane and respiratory irritation. Homopolymer of hexamethylene diisocyanate has been shown to cause respiratory sensitization. Symptoms include dryness of the throat, tightness of chest and difficulty in breathing. Symptoms may be delayed for several hours after exposure.

This product can produce asthmatic sensitization upon a single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. The allergic respiratory reaction may be life threatening.

Ingestion: Swallowing may cause gastrointestinal irritation abdominal pain, nausea, vomiting and diarrhea.

Skin contact: Skin contact may cause mild irritation with redness, itching and swelling. May cause allergic skin reaction. Homopolymer of hexamethylene diisocyanate has been shown to be mildly irritating to rabbit skin. Animal tests have indicated that respiratory sensitization can result from skin contact with isocyanates.

Eye contact: May cause mild irritation with redness, tearing, stinging and swelling. Homopolymer of hexamethylene diisocyanate has been shown to cause slightly irritating to rabbit eyes.

Chronic effects from short- and long-term exposure: Prolonged exposure to diisocyanates or polyisocyanates may cause chronic irritation, decreased lung function and lung damage and conjunctivitis.

Reproductive Toxicity: This product is not expected to cause adverse reproductive or developmental effects.

Sensitization: Hexamethylene-1,6-diisocyanate has been shown to cause sensitization in a guinea pig maximization test.

Mutagenicity: Homopolymer of hexamethylene diisocyanate was negative the in the AMES test (with/without metabolic activation)

Carcinogenicity: None of the components are listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Homopolymer of hexamethylene diisocyanate: Oral rat LD50 >5,000 mg/kg; Inhalation rat LC50 390-453 mg/m³/4 hr; Dermal rabbit LD50 >5,000 mg/kg.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Homopolymer of hexamethylene diisocyanate: 96 hr LC0 Brachydanio rerio >100 mg/L; 48 hr EC0 daphnia magna >100 mg/L; 72 hr EC50 Scenedesmus subspicatus >1,000 mg/L

Persistence and degradability: Homopolymer of hexamethylene diisocyanate is not readily biodegradable.

Bioaccumulative potential: Not expected to bioaccumulate.

Mobility in soil: No data available.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations. Incineration is the preferred method.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None
IMDG	None	Not Regulated	None	None	None
IATA	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions:

15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health, Chronic Health

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects): None

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian CEPA: All of the ingredients in this product are listed on the Canadian DSL.

Canadian WHMIS Classification: Class D Division 2 Subdivision A (Very Toxic Material Causing other Toxic Effects), Class D Division 2 Subdivision B (Toxic Material Causing other Toxic Effects)

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 2 Flammability = 1 Instability = 1
HMIS Rating: Health = 2* Flammability = 1 Physical Hazard = 1

SDS Revision History: New SDS

Date of preparation: January 6, 2014

Date of last revision: New SDS

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT

TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED
HEREIN AND USE.

Accelera Resin SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Accelera Resin, Accelera LH Resin

Product Code:

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: January 6, 2014

2. HAZARD(S) IDENTIFICATION

This product is one part of a 3 part product. Read and understand the hazard information on the SDS for Accelera Hardener before using this product.

Classification:

Physical	Health
Not Hazardous	Skin Irritation Category 2 Eye Irritation Category 2 Skin Sensitization Category 1 Specific Target Organ Toxicity – Single Exposure Category 3 (Respiratory Irritation)

Labeling:

Warning!



Hazard statement(s)

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary statement(s)

Avoid breathing vapors or spray.
Use only outdoors or in a well-ventilated area.
Wash thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves, eye protection and face protection.
IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER if you feel unwell.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Secondary diamines	Proprietary	50-100%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get medical attention.

Skin contact: Remove contaminated clothing. Immediately wash skin thoroughly with soap and water for 20 minutes. If rash or irritation develops, get medical attention. Launder clothing before re-use.

Eye contact: Immediately flush with large quantities of water for 15 minutes, holding the eyelids apart. Get medical attention if irritation persists.

Ingestion: If conscious, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

Notes to Physicians: Application of a corticosteroid cream has been effective in treating skin irritation.

Most important symptoms/effects, acute and delayed: May be irritating to eyes, skin and respiratory tract. May cause allergic skin reaction.

Indication of immediate medical attention and special treatment, if necessary: If a skin reaction occurs, get medical attention. Symptoms may be delayed for several hours after exposure.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use alcohol foam, carbon dioxide and dry chemical. Cool fire exposed containers with water.

Specific hazards arising from the chemical: Ammonia gas may be liberated at high temperatures. Combustion may produce carbon and nitrogen oxides.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing as described in Section 8. Isolate the area and prevent access. Ventilate and remove ignition sources.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and materials for containment and cleaning up: Contain and collect with an inert absorbent. Place into an appropriate container for disposal,

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Wash thoroughly after handling and before eating, drinking, smoking or using the toilet. Use with adequate ventilation.

Conditions for safe storage, including any incompatibilities: Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from physical damage. Store away from oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Secondary diamines	None Established
--------------------	------------------

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to minimize exposures.

Individual protection measures, such as personal protective equipment:

Respiratory protection: If the exposures are excessive, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Wear impervious gloves such as nitrile rubber or polyvinyl alcohol.

Eye protection: Chemical safety goggles recommended.

Other: Impervious clothing as needed to prevent contact. An eye wash should be available in the immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Light yellow liquid

Odor: Slight odor

Odor threshold: Not available	pH: Not available
Melting Point/Freezing Point: - Not available	Boiling Point: Not available
Flash point: >200 °F / >93.4°C	Evaporation rate: Not available

Flammability (solid, gas): Not flammable	
Flammable limits: LEL: Not available	UEL: Not available
Vapor pressure: Not available	Vapor density: Not applicable
Relative density: 1.0535	Solubility(is): Not available
Partition coefficient: n-Octanol/water: Not applicable	Auto-ignition temperature: Not available
Decomposition temperature: Not available	Viscosity: Not available

10. STABILITY AND REACTIVITY

Reactivity: None known.

Chemical stability: Stable

Possibility of hazardous reactions: Ammonia gas may be liberated at high temperatures. N-Nitrosamines may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations.

Conditions to avoid: Avoid excessive heat.

Incompatible materials: Avoid contact with oxidizing agents.

Hazardous decomposition products: Thermal decomposition may produce carbon and nitrogen oxides, ammonia, nitrosamines and nitric acid.

11. TOXICOLOGICAL INFORMATION

Inhalation: Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin contact: Skin contact may cause irritation. May cause allergic skin reaction.

Eye contact: May cause irritation with redness, tearing, stinging and swelling.

Chronic effects from short- and long-term exposure: No chronic effects are expected.

Reproductive Toxicity: This product is not expected to cause adverse reproductive or developmental effects.

Sensitization: Secondary diamines may cause skin sensitization.

Mutagenicity: This product is not expected to cause mutagenic activity.

Carcinogenicity: None of the components are listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Secondary diamines: No toxicity data available.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Secondary diamines: No data available

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None
IMDG	None	Not Regulated	None	None	None
IATA	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions:

15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects): None

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian WHMIS Classification: Class D Division 2 Subdivision B (Toxic Material Causing other Toxic Effects)

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 2 Flammability = 1 Instability = 0
HMIS Rating: Health = 2 Flammability = 1 Physical Hazard = 0

SDS Revision History: New SDS

Date of preparation: January 6, 2014

Date of last revision: New SDS

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND USE.

Poly-Crete Hardener: MD, SL, HF, TF and NATURAL SL SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Poly-Crete Hardener: MD, SL, HF, TF, and NATURAL SL

Product Code:

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: January 9, 2014

2. HAZARD(S) IDENTIFICATION

This product is one part of a 3 part product. Read and understand the hazard information on the SDS for Poly-Crete Resin before using this product.

Classification:

Physical	Health
Not Hazardous	Acute Toxicity Category 4 – Inhalation Eye Irritation Category 2 Skin Irritation Category 2 Skin Sensitization Category 1 Respiratory Sensitization Category 1 Specific Target Organ Toxicity – Single Exposure Category 3 (Respiratory Irritation) Specific Target Organ Toxicity – Repeat Exposure Category 2

Labeling:

Danger!



Hazard statement(s)

Harmful if inhaled.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Causes serious eye irritation.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause respiratory irritation.
 May cause damage to lungs through prolonged or repeated inhalation exposure.

Precautionary statement(s)

Do not breathe mist, vapors or spray.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing should not be allowed out of the workplace.
 Wash thoroughly after handling.
 Wear protective gloves, eye protection and face protection.
 In case of inadequate ventilation wear respiratory protection.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical attention.
 Take off contaminated clothing and wash it before reuse.
 IF IN EYES: Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical attention.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER if you feel unwell.
 Get medical attention if you feel unwell.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
4,4'-Diphenylmethane diisocyanate	101-68-8	40-60%
Polyisocyanate based on MDI	Proprietary	40-60%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Immediately remove to fresh air. If breathing is difficult have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get immediate medical attention. Asthma-like symptoms may develop immediately or delayed up to several hours.

Skin contact: Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. If rash or irritation develops, get medical attention. Launder clothing before re-use.

Eye contact: Immediately flush with large quantities of water for 15 minutes, holding the eyelids apart. Get medical attention if irritation develops.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. DO NOT INDUCE VOMITING. Get medical attention.

Most important symptoms/effects, acute and delayed: Irritating to eyes, skin and respiratory system. May cause allergic skin and respiratory reaction. If an allergic respiratory reaction occurs, get immediate medical attention. Symptoms may be delayed. Individuals sensitized to isocyanates may have a life-threatening allergic reaction.

Indication of immediate medical attention and special treatment, if necessary: If skin or respiratory sensitization occurs, get immediate medical attention. Symptoms may be delayed for several hours after exposure. Respiratory sensitization may be life threatening.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use foam, carbon dioxide and dry chemical. Cool fire exposed containers with water.

Specific hazards arising from the chemical: This product reacts with water producing heat and gases. Reaction may be violent. Closed containers may rupture when exposed to extreme heat or contaminated with water. Combustion may produce isocyanate vapors and other irritating, highly toxic gases. Exposure to heated diisocyanates can be extremely dangerous.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Do not allow run-off from fire fighting to enter drains or water courses. Decontaminate equipment and protective clothing before reuse.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing as described in Section 8. Isolate the area and prevent access. Ventilate and remove ignition sources.

Methods and materials for containment and cleaning up: Contain and collect with an inert absorbent. Neutralize with a decontamination solution made up of 90% water and 10% concentrated ammonia and 2% detergent. Use a 10 to 1 ratio. Wait 15 minutes. Collect into a suitable container. Repeat until the surface is completely decontaminated. Cover loosely with lid and allow container to vent for 48 hours to allow carbon dioxide to escape.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe vapors or mists. Use only with adequate ventilation. Wear respiratory protection if material is heated, sprayed, used in a confined space, or if the exposure limit is exceeded. Warning properties are not adequate to prevent overexposure from inhalation. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash thoroughly after handling. Do not breathe smoke and gases created by overheating or burning this material. Decomposition products can be highly toxic and irritating.

Conditions for safe storage, including any incompatibilities: Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Protect from physical damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

4,4'-Diphenylmethane diisocyanate	00.005 ppm TWA ACGIH TLV 0.02 ppm Ceiling OSHA PEL
Polyisocyanate based on MDI	None Established

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

Personal Protective Equipment:

Respiratory protection: If the exposure limits are exceeded or if exposure levels are unknown, a NIOSH approved positive pressure air supplied respirator with a full facepiece or air supplied hood should be used. In some situations where exposure levels are known to be below 10 times the exposure limit an air purifying respirator (organic vapor with particulate prefilter) can be used. A change schedule for cartridges is required. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Wear impervious gloves such as neoprene or butyl rubber.

Eye protection: Chemical safety goggles recommended.

Other: Impervious clothing as needed to prevent contact. A safety shower and eye wash should be available in the immediate work area.

Medical Surveillance: A pre-placement physical should be given to all employees that will work with isocyanates. Employees with a prior isocyanate sensitization should be excluded from working with this product. A history of adult asthma, eczema and respiratory allergies are possible reasons for excluding or restricting the employee from working with this product. A comprehensive annual medical surveillance program should be instituted for all employees who work with isocyanates. Once a worker has been diagnosed as sensitized, no further exposure can be permitted.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Dark amber liquid

Odor: Faint aromatic odor

Odor threshold: 0.384 (MDI)	pH: Not applicable
Melting Point/Freezing Point: Not available	Boiling Point: 392°F / 200°C
Flash point: >392 °F / >200°C	Evaporation rate: Not available
Flammability (solid, gas): Not flammable	
Flammable limits: LEL: Not applicable	UEL: Not applicable
Vapor pressure: 0.00001 mmHg @25°C	Vapor density: 8.5
Relative density: 1.24	Solubility(is): Reacts in Water
Partition coefficient: n-Octanol/water: Not available	Auto-ignition temperature: Not available
Decomposition temperature: Not available	Viscosity: 35 mPas@25°C

10. STABILITY AND REACTIVITY

Reactivity: None known.

Chemical stability: Stable

Possibility of hazardous reactions: Contact with water or temperature greater than 400°F may cause polymerization.

Conditions to avoid: Avoid contact with heat, sparks and flames. Protect from freezing.

Incompatible materials: Avoid contact with water, alcohols, amines, acids and strong bases. May damage plastics and rubber.

Hazardous decomposition products: Thermal decomposition may produce carbon and nitrogen oxides, hydrogen cyanide and aromatic isocyanates.

11. TOXICOLOGICAL INFORMATION

Inhalation: Inhalation of vapors or mists may cause mucous membrane and respiratory irritation. 4,4'-Diphenylmethane diisocyanate has been shown to cause respiratory sensitization. Symptoms include dryness of the throat, tightness of chest and difficulty in breathing. Symptoms may be delayed for several hours after exposure. This product can produce asthmatic sensitization upon a single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. The allergic respiratory reaction may be life threatening.

Ingestion: Swallowing may cause gastrointestinal irritation abdominal pain, nausea, vomiting and diarrhea.

Skin contact: Skin contact may cause irritation with redness, itching and swelling. May cause allergic skin reaction. 4,4'-Diphenylmethane diisocyanate has been shown to be irritating to rabbit skin. Animal tests have indicated that respiratory sensitization can result from skin contact with isocyanates.

Eye contact: May cause irritation with redness, tearing, stinging and swelling. 4,4'-Diphenylmethane diisocyanate has been shown to cause irritation to rabbit eyes.

Chronic effects from short- and long-term exposure: Prolonged exposure to 4,4'-diphenylmethane diisocyanate may cause chronic irritation, decreased lung function and lung damage and conjunctivitis. 4,4'-Diphenylmethane has been shown to cause damage to the olfactory epithelium after repeated inhalation in a repeat dose study in rats.

Reproductive Toxicity: 4,4'-Diphenylmethane diisocyanate has been shown to cause developmental toxicity only at doses that were maternally toxic.

Sensitization: 4,4'-Diphenylmethane diisocyanate has been shown to cause sensitization in a skin sensitization study with guinea pigs.

Mutagenicity: 4,4'-Diphenylmethane diisocyanate was negative the in the AMES test (with/without metabolic activation) and in an in vivo micronucleus assay.

Carcinogenicity: None of the other components are listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

4,4'-Diphenylmethane diisocyanate: Oral rat LD50 >2,000 mg/kg; Inhalation rat LC10 > 2.24 mg/L/1 hr; Dermal rabbit LD50 >9,400 mg/kg.

Polyisocyanate based on MDI: No acute toxicity data available.

12. ECOLOGICAL INFORMATION**Ecotoxicity:**

4,4'-Diphenylmethane diisocyanate: 96 hr LC50 *Oryzias latipes* > 3000 mg/L; 48 hr EC50 *daphnia magna* 129.7 mg/L; 72 hr EC50 *Desmodesmus subspicatus* > 1640 mg/L (structurally similar chemical)

Polyisocyanate based on MDI: No data available

Persistence and degradability: 4,4'-Diphenylmethane diisocyanate is not readily biodegradable.

Bioaccumulative potential: 4,4'-Diphenylmethane diisocyanate has a calculated BCF of 200.

Mobility in soil: No data available.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations. Incineration is the preferred method.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None
IMDG	None	Not Regulated	None	None	None
IATA	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions:

15. REGULATORY INFORMATION

CERCLA: This product has a Reportable Quantity (RQ) of 10,000 lbs. based on the RQ for 4,4'-Diphenylmethane diisocyanate of 5,000 lbs. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under applicable federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health, Chronic Health

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects): None

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian CEPA: All of the ingredients in this product are listed on the Canadian DSL.

Canadian WHMIS Classification: Class D Division 2 Subdivision A (Very Toxic Material Causing other Toxic Effects), Class D Division 2 Subdivision B (Toxic Material Causing other Toxic Effects)

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 2 Flammability = 1 Instability = 1

HMIS Rating: Health = 2* Flammability = 1 Physical Hazard = 1

SDS Revision History: Converted to GHS format. All sections revised.

Date of preparation: January 9, 2014

Date of last revision: New SDS

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND USE.

Poly-Crete HF, MD, SL, TF/WR, & NATURAL SL Resin SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Poly-Crete HF, MD, SL, TF/WR, & NATURAL SL Resin

Product Code:

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: January 30, 2014

2. HAZARD(S) IDENTIFICATION

This product is one part of a 3 part product. Read and understand the hazard information on the SDS for Poly-Crete Hardener and Poly-Crete Aggregate before using this product.

Classification:

Physical	Health
Not Hazardous	Specific Target Organ Toxicity – Repeat Exposure Category 2

Labeling:

Warning!



Hazard statement(s)

May cause damage to kidneys through prolonged or repeated exposure.

Precautionary statement(s)

Do not breathe mist, vapors or spray.
Get medical attention if you feel unwell.
Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Polyester-Ether Polyol Blend	Mixture	1-15%
Diethylene Glycol	111-46-6	1-5%
Titanium Dioxide	13463-67-7	1-5%
Carbon Black	1333-86-4	<1%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Remove victim to fresh air. If irritation occurs or breathing is difficult, get medical attention.

Skin contact: Wash with soap and water. If irritation develops and persists, get medical attention.

Eye contact: Flush with large quantities of water, holding the eyelids apart. Get medical attention if irritation persists.

Ingestion: If conscious, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

Most important symptoms/effects, acute and delayed: Prolonged overexposure to diethylene glycol may cause kidney damage.

Indication of immediate medical attention and special treatment, if necessary: None expected under normal conditions of use. If large amounts are swallowed, get medical attention.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use water spray, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Specific hazards arising from the chemical: Combustion may produce carbon oxides.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing as described in Section 8.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and materials for containment and cleaning up: Contain and collect with an inert absorbent. Place into an appropriate container for disposal. Caution slip hazard. Wash spill site with soap and water.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Wash thoroughly after handling and before eating, drinking, smoking or using the toilet. Use with adequate ventilation.

Conditions for safe storage, including any incompatibilities: Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from physical damage. Store away from oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Polyol Blend	None Established
Diethylene Glycol	10 mg/m ³ TWA AIHA WEEL
Titanium Dioxide	15 mg/m ³ TWA OSHA PEL (total dust) 10 mg/m ³ TWA ACGIH TLV
Carbon Black	3.5 mg/m ³ TWA OSHA PEL 3 mg/m ³ TWA ACGIH TLV (inhalable)

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposures below occupational exposure limits.

Personal Protective Equipment:

Respiratory protection: If the exposures are excessive, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Wear impervious gloves such as nitrile or butyl rubber.

Eye protection: Chemical safety goggles recommended.

Other: Impervious clothing as needed to prevent contact. An eye wash should be available in the immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Colored, viscous liquid

Odor: Faint aromatic odor

Odor threshold: Not available	pH: Not available
Melting Point/Freezing Point: - Not available	Boiling Point: 212°F / 100°C
Flash point: 540 °F / 282.2°C	Evaporation rate: <1 (butyl acetate = 1)
Flammability (solid, gas): Not applicable	
Flammable limits: LEL: Not applicable	UEL: Not applicable

Vapor pressure: Not available	Vapor density: >1
Relative density: >1	Solubility: Dispersible in water
Partition coefficient: n-Octanol/water: Not available	Auto-ignition temperature: Not available
Decomposition temperature: Not available	Viscosity: Not available

10. STABILITY AND REACTIVITY

Reactivity: None known.

Chemical stability: Stable

Possibility of hazardous reactions: None known.

Conditions to avoid: Avoid excessive heat.

Incompatible materials: Avoid contact with oxidizing agents.

Hazardous decomposition products: Thermal decomposition may produce carbon oxides.

11. TOXICOLOGICAL INFORMATION

Inhalation: Excessive inhalation of mists may cause mucous membrane and upper respiratory tract irritation.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea and diarrhea.

Skin contact: Prolonged skin contact may cause irritation.

Eye contact: May cause irritation with redness and tearing.

Chronic effects from short- and long-term exposure: Prolonged overexposure to diethylene glycol has been shown to cause kidney damage in animal studies.

Reproductive Toxicity: This product is not expected to cause adverse reproductive or developmental effects.

Sensitization: None of the components have been shown to cause sensitization in humans or animals. .

Mutagenicity: This product is not expected to cause mutagenic activity.

Carcinogenicity: Carbon black is listed as "Possibly Carcinogenic to Humans" (Group 2B) by IARC. Carbon black is inextricably bound in a polymer matrix and no exposure occurs during use.

Acute Toxicity Values:

Polyol Blend: No toxicity data available.

Diethylene glycol: Oral rat LD50 12,565 mg/kg; Dermal rabbit LD50 11,890 mg/kg

Titanium Dioxide: Oral rat LD50 >5000 mg/kg; Inhalation rat LC50 > 6.82 mg/L /4 hr

Carbon Black: Oral rat LD50 >8000 mg/kg; Inhalation rat LC50 > 4.6 mg/m³/4 hr

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Polyol Blend: No data available

Diethylene glycol: 96 hr LC50 *Lepomis macrochirus* 1000 mg/L;

Titanium Dioxide: 72 hr EC50 *Pseudokirchnerella subcapitata* 61 mg/L

Carbon Black: 96 hr Danio rerio LC0 1000 mg/L; 24 hr EC50 daphnia magna >5600 mg/L; 72 hr EC50 >10000 mg/L

Persistence and degradability: Biodegradation is not applicable to inorganic substances such as carbon black and titanium dioxide. Diethylene glycol is readily biodegradable.

Bioaccumulative potential: Diethylene glycol has a BCF of 3. .

Mobility in soil: Diethylene glycol has a high mobility in soil.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None
IMDG	None	Not Regulated	None	None	None
IATA	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions:

15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects): Toluene 108-88-3 (developmental, female reproductive toxicity) <1 ppm, Benzene (71-43-2) (cancer, developmental, male reproductive toxicity) <1 ppm, Ethylbenzene (100-41-4) (cancer) <1 ppm (carbon black, crystalline silica and titanium dioxide are inextricably bound).

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian WHMIS Classification: Class D Division 2 Subdivision B (Toxic Material Causing other Toxic Effects)

This product has been classified under the CPR and this SDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 1 Flammability = 1 Instability = 0

HMIS Rating: Health = 1 Flammability = 1 Physical Hazard = 0

SDS Revision History: Converted to GHS format. All sections revised

Date of preparation: January 30, 2014

Date of last revision: New SDS

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. **MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND USE.**

Poly-Crete Aggregate MD, SL, HF and TF/WR SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Poly-Crete Aggregate MD, SL, HF and TF/WR

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: January 13, 2014

2. HAZARD(S) IDENTIFICATION

This product is one part of a 3 part product. Read and understand the hazard information on the SDS for Poly-Crete Resin and Poly-Crete Hardener before using this product.

Classification:

Physical	Health
Not Hazardous	Skin Irritation Category 2 Eye Damage Category 1 Skin Sensitization Category 1 Specific Target Organ Toxicity – Single Exposure Category 3 (Respiratory Irritation) Carcinogenicity Category 1A Specific Target Organ Toxicity – Repeat Exposure Category 1

Labeling:

Danger!



Hazard statement(s)

Causes skin irritation.
Causes serious eye damage.
May cause an allergic skin reaction.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

May cause respiratory irritation.
 May cause cancer by inhalation.
 Causes damage to lungs through prolonged or repeated inhalation exposure.

Do not breathe dust, fume.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing should not be allowed out of the workplace.
 Wear protective gloves, protective clothing, eye protection or face protection.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical attention.
 Take off contaminated clothing and wash it before reuse.
 IF IN EYES: Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a POISON CENTER or doctor.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER if you feel unwell.
 IF exposed or concerned: Get medical attention.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Portland Cement	65997-15-1	5-95%
Crystalline Silica	14808-60-7	0-90%
Calcium Sulfate	7778-18-9	0-10%
Iron Oxide	1309-37-1	0-15%
Calcium Carbonate	1317-65-3	0-5%
Magnesium Oxide	1309-48-4	0-5%
Calcium Oxide	1305-78-8	0-5%
Calcium Hydroxide	1305-62-0	0-5%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial ventilation. Get medical attention if irritation persists.

Skin contact: Remove contaminated clothing and launder before reuse. Wash skin with a cool water and pH-neutral soap. Get medical attention if irritation develops or persists.

Eye contact: Immediately flush eyes with large quantities of water for at least 15 minutes, holding the eyelids apart. Get immediate medical attention.

Ingestion: If swallowed, drink 1 or 2 glasses of water to dilute. Never give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

Most important symptoms/effects, acute and delayed: Dust may cause eye and skin irritation or burns. Wet cement may cause eye and skin damage. May cause skin sensitization. Inhalation of dust may cause mucous membrane and respiratory irritation. Prolonged overexposure to respirable crystalline silica may cause lung disease (silicosis) and increase the risk of lung cancer. Risk of cancer depends on duration and level of exposure

Indication of immediate medical attention and special treatment, if necessary: If eye or skin burns occur, get immediate medical attention. For ingestion, get immediate medical attention.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use media appropriate to the surrounding fire.

Specific hazards arising from the chemical: None known.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing as described in Section 8.

Environmental precautions: Report releases as required by local and federal authorities.

Methods and materials for containment and cleaning up: Collect using dustless method and place in appropriate container for use or disposal. Do not use compressed air.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with the eyes and skin. Do not breathe dust. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation and proper dust collection methods to keep exposure level below occupational exposure limits. Wash thoroughly with soap and water after use.

Empty containers retain product residues. Follow all SDS precautions in handling empty containers.

Conditions for safe storage, including any incompatibilities: Keep dry until ready to use. Store in a cool, dry, well ventilated area away from incompatible materials. Protect from physical damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Portland Cement	5 mg/m ³ TWA OSHA PEL 10 mg/m ³ TWA ACGIH TLV
Crystalline Silica	<u>10 mg/m³</u> TWA OSHA PEL (respirable fraction) % Silica + 2 0.025 mg/m ³ TWA ACGIH TLV (respirable fraction)
Calcium Sulfate	5 mg/m ³ TWA OSHA PEL (respirable fraction) 10 mg/m ³ TWA OSHA PEL (total dust) 10 mg/m ³ TWA ACGIH TLV (inhalable fraction)
Iron Oxide	10 mg/m ³ TWA OSHA PEL (fume) 5 mg/m ³ TWA ACGIH TLV (respirable fraction)
Calcium Carbonate	5 mg/m ³ TWA OSHA PEL (respirable fraction) 10 mg/m ³ TWA OSHA PEL (total dust)
Magnesium Oxide	15 mg/m ³ TWA OSHA PEL (fume total particulate) 10 mg/m ³ TWA ACGIH TLV (inhalable fraction)
Calcium Oxide	5 mg/m ³ TWA OSHA PEL 2 mg/m ³ TWA ACGIH TLV
Calcium Hydroxide	5 mg/m ³ TWA OSHA PEL (respirable fraction) 10 mg/m ³ TWA OSHA PEL (total dust) 5 mg/m ³ TWA ACGIH TLV

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

Individual protection measures, such as personal protective equipment:

Respiratory protection: If the exposure limits are exceeded a NIOSH approved particulate respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 or other applicable regulations and good industrial hygiene practice.

Skin protection: Alkali/abrasive resistant gloves are recommended to prevent skin contact.

Eye protection: Chemical safety goggles are recommended to prevent eye contact.

Other: Impervious clothing as needed to avoid skin contact and contamination of personal clothing. A safety shower and eye wash should be available in the immediate work area. If clothing becomes contaminated with dust or wet cement, remove immediately and launder before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Tan granular solid

Odor: No odor

Odor threshold: Not applicable	pH: Not available
Melting Point/Freezing Point: - Not available	Boiling Point: 4000°F / 2204°C
Flash point: Not flammable	Evaporation rate: Not applicable
Flammability (solid, gas): Not flammable or combustible	

Flammable limits: LEL: Not applicable	UEL: Not applicable
Vapor pressure: Not applicable	Vapor density: Not applicable
Relative density: >1	Solubility(is): Insoluble
Partition coefficient: n-Octanol/water: Not applicable	Auto-ignition temperature: Not applicable
Decomposition temperature: Not available	Viscosity: Not applicable

10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable.

Possibility of hazardous reactions: Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride.

Conditions to avoid: Unintentional contact with water will result in hydration and produce caustic calcium hydroxide.

Incompatible materials: Avoid contact with hydrofluoric acid and oxidizing agents.

Hazardous decomposition products: None known.

11. TOXICOLOGICAL INFORMATION

Inhalation: Inhalation of dust may cause irritation to the nose, throat and upper respiratory tract with coughing and shortness of breath.

Ingestion: Large amounts may cause gastrointestinal irritation or burns with nausea and diarrhea.

Skin contact: Contact with dry powder may cause drying of the skin and mild irritation. May cause mechanical irritation. Contact with wet cement may cause irritation with thickening, cracking and fissuring of the skin. Prolonged contact may cause skin burns. May cause allergic skin reaction.

Eye contact: Dust may cause irritation or redness with inflammation of the cornea. May cause mechanical irritation. Direct contact with wet cement or large amounts of dry powder may cause irritation or burns with possible blindness.

Chronic effects from short- and long-term exposure: Chronic inhalation of respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Reproductive Toxicity: None of the components greater than 0.1% have been shown to cause reproductive or developmental toxicity.

Sensitization: Portland cement may contain trace amounts of chromium salts or nickel compounds that have been shown to cause sensitization in humans.

Mutagenicity: None of the components greater than 0.1% have been shown to cause germ cell mutagenicity.

Carcinogenicity: Crystalline silica quartz is listed as "Carcinogenic to Humans" (Group 1) by IARC and "Known to be a Human Carcinogen" by NTP. None of the other components are listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Portland Cement: No toxicity data available

Crystalline Silica, Quartz: Oral rat LD50 >22,500 mg/kg

Calcium Sulfate: Oral rat LD50 >1581 mg/kg; Inhalation rat LC50 > 2.61 mg/L/4 hr

Iron Oxide: Oral rat LD50 > 10000 mg/kg;

Calcium Carbonate: No toxicity data available

Magnesium Oxide: No toxicity data available

Calcium Oxide: Oral rat LD50 > 2000 mg/kg

Calcium Hydroxide: Oral rat LD50 > 2000 mg/kg; Dermal rabbit LD50 > 2500 mg/kg

12. ECOLOGICAL INFORMATION**Ecotoxicity:**

Portland Cement: No toxicity data available

Iron Oxide: 96 hr LC50 Brachydanio rerio 100000 mg/L; 48 hr EC50 daphnia magna >100 mg/L

Calcium Carbonate: No data available

Magnesium Oxide: No data available

Calcium Oxide: 96 hr LC50 Oncorhynchus mykiss 50.6 mg/L; 48 hr EC50 daphnia magna 49.1 mg/L; 72 hr

EC50 Pseudokirchnerella subcapitata 184.57 mg/L

Crystalline Silica: 72 hr LC50 carp >10,000 mg/L

Calcium Hydroxide: 96 hr LC50 Gasterosteus aculeatus 457 mg/L; 48 hr EC50 daphnia magna 49.1 mg/L; 72 hr

EC50 Pseudokirchnerella subcapitata 184.57 mg/L

Persistence and degradability: Biodegradation is not applicable to inorganic substances.**Bioaccumulative potential:** Not expected to be bioaccumulative.**Mobility in soil:** No data available.**Other adverse effects:** None known.**13. DISPOSAL CONSIDERATIONS**

Dispose in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None
IMDG	None	Not Regulated	None	None	None
IATA	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health, Chronic Health

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects): Crystalline silica, quartz (14808-60-7) 0-95% cancer, Titanium dioxide (13463-67-7) <0.08% (cancer)

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian WHMIS Classification: Class D Division 2A, Class D Division 2B

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 3 Flammability = 0 Instability = 0

HMIS Rating: Health = 3* Flammability = 0 Physical Hazard = 0

SDS Revision History: All sections revised – Converted to GHS forma

Date of preparation: January 13, 2014

Date of last revision: New SDS

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND USE.