

DUR-A-FLEX
Pool Deck Registration/Installation Form
(Facility Owner Copy)

Warning

REGISTRATION FORMS

Every pool deck installation must be registered with a Dur-A-Flex, Inc. Sales representative at the completion of installation and before the pool deck is open for use.

These forms can be found in the Technical Catalog in the Master Documents section or at www.dur-a-flex.com

CLEANING

Warning

Pool decks are predominately wet surfaces that will require daily cleaning with E-Z Clean detergent to aid in the removal of dirt, grime, debris, lotions, soaps and oils.

Without a regular maintenance program to remove the accumulation of the above mentioned contaminates, there is an increased risk of slip and fall accidents.

To remove hard water deposits (lime scale), periodic use of an acid based cleaner such as "Lime Away" can be used.

Our local sales representative will provide you with a complimentary one gallon sample of E-Z Clean detergent to assist your housekeeping efforts.

For proper cleaning instructions, please refer to our cleaning guidelines in the Contractor Center at www.dur-a-flex.com. Or in our Technical Catalog in the Master Documents section. A floor cleaning training video is also available on our website.

Additional quantities of E-Z Clean detergent may be purchased by calling Dur-A-Flex at 800-253-3539.

Signatures

Local Dur-A-Flex Sales Representative: _____ Date: _____

Pool Contact: _____ Date: _____

DUR-A-FLEX
Pool Deck Registration/Installation Form
(DAF use only)

Pool Deck User Contact Information

Facility Name: _____ Telephone Number: _____

Street Address: _____

City/State/Zip: _____

Contact Name: _____ Position: _____

Pool Deck System Information

DFC: _____

Installed Resinous System: _____

Installation Date: _____

Square Footage of Resinous System: _____

Cleaning Method:

Mechanized Floor Scrubber Deck Brush High Pressure Water 2000-3000 PSI

Cleaning must be performed prior to slip meter testing

Slip Meter Test Results: Wet: _____ Dry: _____

Note: For multiple test locations, draw a schematic on back of this sheet and record.

OSHA guideline for a safe traction surface is a coefficient of Friction of 0.5 (dry test)

ADA guideline for a safe traction surface is a coefficient of Friction of 0.6 (dry test)

RETURN TO:
DUR-A-FLEX
ATTN: LAB
File in INDEX