



95 Goodwin Street East Hartford, CT 06108

Tel: 800-253-3539 • Fax: 860-528-2802 • Internet: www.dur-a-flex.com • E-Mail: contact us@dur-a-flex.com

DUR-A-GRIP

DESCRIPTION

DUR-A-GRIP is a granulated polymer additive that is used to increase slip resistance. This product is best suited for interior and exterior foot traffic areas. DUR-A-GRIP is mixed directly into the resin just before application.

BENEFITS

- Increased Slip Resistance
- Durable
- Easy to Apply
- Works Well in Wet Areas
- UV Stable

TYPICAL USES

DUR-A-GRIP is recommended for:

- ARMOR TOP
- POLY-THANE #2 HIGH SOLIDS
- CRYL-A-TOP T-301, T-303

DUR-A-GRIP is **NOT** recommended for:

- DUR-A-GLAZE #4
- DUR-A-GLAZE #5
- DUR-A-GLAZE NOVOLAC
- DUR-A-GARD
- ACCELERA

ESTIMATING TOOL

To estimate how much DUR-A-GRIP will be needed, divide the total square footage of the job by the spread rate of the topcoat being used. This equals the total number of gallons of topcoat. Multiplying the total number of gallons of topcoat by 6 will equal the total number of ounces of DUR-A-GRIP needed for the job.

Reference guide for 3 volume ounce per gallon:

- 1 Quart for 10 gallons of resin
- 1 Gallon for 40 gallons of resin
- 5 Gallons for 200 gallons of resin

APPLICATION METHOD

DUR-A-GRIP is used at 1 to 3 volume ounces per mixed gallon (1 ounce for light slip resistant surface areas, 3 ounces for greater slip resistance surface areas). To achieve the best results, DUR-A-GRIP is only to be used in the final topcoat of the flooring system. Follow the topcoat instructions and add DUR-A-GRIP directly into the mix. Make sure DUR-A-GRIP is mixed into the resin for a minimum of 30 seconds. Apply the mixture according to the recommended application method and spread rate of the topcoat.

LIMITATIONS

Once DUR-A-GRIP is added to the resin, use immediately to avoid the product from floating to the surface. NOTE: The addition of DUR-A-GRIP may alter the overall appearance of the floor system.

PACKAGING

DUR-A-GRIP is available in 1-quart, 1-gallon and 5-gallon pails.

CAUTION

Material may build a static charge when being handled. Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. **KEEP OUT OF REACH OF CHILDREN.**

Before using any DUR-A-FLEX, Inc. product, be sure the Safety Data Sheet is read and understood.